

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000065

International filing date: 12 January 2005 (12.01.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0400572.4
Filing date: 12 January 2004 (12.01.2004)

Date of receipt at the International Bureau: 02 March 2005 (02.03.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



INVESTOR IN PEOPLE


The Patent Office
 Concept House
 Cardiff Road
 Newport
 South Wales
 NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 21 February 2005



70



13 JAN 04 08:47:24-1 D02000
P01/7700 0.00 0400572.4 NONE



The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

MCM/MPL/26133

2. Patent application number

(The Patent Office will fill in this part)

0400572.4

12 JAN 2004

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

Helmet Integrated Systems Limited
Unit 3, Focus 4
Fourth Avenue
Letchworth
Hertfordshire SG6 2TU
United Kingdom

8569824001

4. Title of the invention

Headgear

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

MATHYS & SQUIRE
100 Gray's Inn Road
London WC1X 8AL
United Kingdom

1081001 ✓

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	14
Claim(s)	6
Abstract	1
Drawing(s)	11 + 11 RM

10. If you are also filing any of the following, state how many against each item.

Priority documents	-
Translations of priority documents	-
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	-
Request for preliminary examination and search (Patents Form 9/77)	-
Request for substantive examination (Patents Form 10/77)	-
Any other documents (please specify)	-

11. I/We request the grant of a patent on the basis of this application.
 Signature M Mathys & Squire Date 12/1/04
 MATHYS & SQUIRE

12. Name and daytime telephone number of person to contact in the United Kingdom
 Michael C Moir - 020 7830 0000

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

HEADGEAR

The present invention relates to headgear. In particular, the invention relates to a personalised internal cap for a helmet, a helmet comprising a personalised internal cap, a method of manufacturing such a helmet and protective apparel comprising
5 such a helmet, wherein the internal cap is personalised such that the helmet sits in a predetermined position on a wearer's head.

The invention is particularly suitable for the fitting of helmets for pilots of military
10 aircraft. Such helmets typically comprise an outer protective helmet and, attached to the outer helmet, a helmet mounted display system. Such systems require exact and repeatable placement of images in front of the wearer's eyes during flight. A poorly-fitting helmet tends to move relative to the head during use, thus causing the display to be displaced out of the line of sight of the wearer. A poorly-fitting helmet
15 also causes the weight of the helmet to be focussed on pressure points, resulting in user discomfort.

However, in certain applications, it is necessary for the wearer to wear additional clothing to protect him from the environment in which he is to work. In particular, a
20 protective hood might be worn under the helmet. This may result in the helmet not sitting in the necessary position for acceptable operation of the external equipment.

It is an aim of at least some embodiments of the invention to overcome or alleviate this and/or other problems.

25 Therefore, in accordance with a first aspect of the invention, there is provided a personalised cap for a helmet, the cap being bespoke to a specific wearer so as precisely to fit the helmet to the wearer's head, the cap comprising a crown portion and a separate brow portion, the crown and brow portion being contiguous with each
30 other.

Preferably, the brow portion interlocks with the crown portion, so that relative

movement of the portions in use may be minimised.

Preferably, at least one said portion is of impact or energy absorbing material. This may result in increased protection of the head of a wearer.

5

Preferably, the brow portion is thinner than the crown portion, since this may allow for the mounting of helmet-mounted equipment closer to the eyes of a wearer and and for the distance of an image presented by a helmet mounted display from the eyes of a wearer to be constant.

10

Preferably, the brow portion is of a different impact or energy absorbing material to the crown portion.

A second aspect provides a helmet comprising a personalised cap as set out above.

15

Preferably, a brow portion of the helmet is of a smaller radius than a crown portion to permit the attachment over the helmet brow portion of a helmet-mounted display equipment. This also may result in the location of the equipment close to the eyes of the wearer of the helmet.

20

Preferably, the brow portion of the cap is removable from the helmet without disturbing the crown portion, whereby one brow portion can be substituted for another.

25 A further aspect provides a method of manufacturing a helmet comprising a personalised internal cap which positions the helmet on the wearer's head, the method comprising a prior determination of the shape of the wearer's head by a measurement device followed by the production of a kit of parts for assembly into said personalised cap, the kit comprising a crown portion and alternative brow
30 portions, a first said brow portion conforming to the wearer's head when wearing an environmental protection hood, and a second said brow portion conforming to the wearer's head without said hood.

Preferably, the measurement device is a non-contact measuring device.

Preferably, during the prior determination the relative positions of the wearer's eyes and the measured portion of his head are determined.

5

Yet a further aspect provides a kit of parts for precisely fitting a helmet to a wearer's head, the kit comprising a crown portion and first and second brow portions of a personalised internal cap which position the helmet on the wearer's head, the first and second brow portions having respectively been produced to align the helmet on the wearer's head to a predetermined position relative to his eyes when the wearer respectively is wearing and is not wearing an environmental protection hood.

10

The individual components of the kit of parts may also be provided separately; or in any combination. Thus the invention also provides a crown portion of a personalised cap for a helmet, the crown portion conforming to the shape of a wearer's head. The invention also provides, independently, first and second brow portions of a personalised cap for a helmet, the brow portions conforming to the shape of a particular wearer's head when not wearing and when wearing an environmental protection hood, respectively.

15
20

Preferably in such a method or kit of parts, the crown portion engages the first brow portion or the second brow portion to form the personalised internal cap.

A related aspect of the invention provides a helmet comprising a personalised internal cap formed from a kit of parts as set out above, and a further aspect provides protective apparel comprising such a helmet or a helmet as set out above.

25

Yet a further aspect of the invention provides an environmental protection hood for use under a protective helmet, comprising an aperture containing a window adjacent the periphery of which is provided means for engaging with an opening in a helmet.

30

In this way, the window may be positively located with respect to the helmet. This may result in the minimising of optical effects due to a wearer looking through both the window and the visor of the helmet.

- 5 The window is preferably reversibly removable from the hood. This may allow for increased comfort in the event the hood is donned out of anticipated rather than actual necessity. In which case, the window might be removed until necessity for the hood arises, thereby keeping the wearer cooler.
- 10 In an example, engaging means are provided for engaging with and retaining the window, which engaging means are preferably mounted on a rigid frame.

Preferably, the hood further comprises fittings for engaging with a respiratory mask to locate such a mask when used by a wearer of the hood. The provision of fittings on the hood for attaching a mask rather than attaching the mask to the helmet may divorce the location of the mask from that of the helmet, in a hood formed of a flexible material. This may provide increased comfort for the wearer, particularly when under exertion.

- 20 Preferably, the hood further comprises a removable mask portion. The provision of a removable mask portion of the hood, for example, around the mouth (and preferably nose) of the wearer, such that when the portion is removed the mouth (and nose) are exposed, may increase the comfort of the wearer of the hood in an analogous way as the provision of a removable window.

25

Preferably, the mask portion comprises a further rigid frame adapted to seal against the rigid frame. This may allow the removable mask portion to be reattached to the main body of the hood rapidly and securely.

- 30 The fittings for attaching a mask are preferably provided on the rigid frame of the mask portion, since this may allow the mask portion and mask to be attached and removed in one operation.

Yet a further aspect of the invention provides an environmental protection hood for use over a helmet and a respiratory mask; the hood being adapted to entirely enclose the helmet and mask.

5

Such a hood may eliminate the need for decontamination of a helmet and mask or for the discarding of the helmet and mask, which may be necessary when using hoods in which the helmet and mask are exposed. In addition, masks used with such a hood need themselves be protective, and a wearer may use a single mask
10 regardless of whether a hood is to be worn.

15

The hood comprises an aperture having situated therein a window through which a wearer of the hood may see, a selectively releasable seal being provided adjacent an edge of the window such that an opening may be made in the hood. In this way, the wearer of the hood may easily create an opening in the hood in conditions where the wearing of the hood is not necessary (but may be anticipated), thereby increasing his comfort. This feature is also provided independently.

20

The hood may preferably be worn with a helmet having a front portion which may be raised and lowered by the wearer and it therefore preferably comprises means for engaging the window with a raisable front portion of a helmet, such that when the hood and helmet are worn together, the window and the front portion of the helmet may be raised and lowered together. This may further server to increase the comfort of the wearer.

25

Preferably, the hood further comprises fittings for engaging with a respiratory mask to locate such a mask when used by a wearer of the hood.

30

Hoods in accordance with the preceding aspects of the invention (whether for use over of under a helmet) preferably further comprise a sleeve adapted to receive a hose for delivering air to a respiratory mask worn by a wearer of the hood. In this way, it is not necessary that the hose itself is protective since it is enclosed by the

sleeve. A single hose may therefore be used regardless of whether a hood is to be worn. This feature is also provided independently.

5 The sleeve is preferably formed of the same material as the hood so that it too forms part of the enclosure of the hood, which thereby also protects the hose.

Preferably, the distal end of the sleeve with respect to the aperture of the hood has means inside the sleeve for engaging with a hose by means of which the hose may be fed with air and means outside the sleeve for engaging with an air supply means
10 of an aircraft, by means of which the hose may be fed with air.

The sleeve preferably further comprises at its distal end means for attaching a further hose for providing demisting air to the hood adjacent the head of a wearer and has a further hose for providing that demisting air which runs within the sleeve
15 from its distal end to a portion of the hood adapted in use to be adjacent the head of a wearer, where it may be directed, for example, onto the inside of the window of the hood.

A further aspect of the invention provides a respiratory mask air supply hose
20 comprising enclosure means forming a conduit through which air may pass and structural means for maintaining the cross-section of the conduit, the enclosure means being formed of different material.

In comparison with known hoses which are formed entirely of moulded silicone and
25 which have integral ribs to maintain the structure of the hose, such a hose may be made to be lighter by selection of an appropriate material for the structural means, which may in turn result in greatly reduced load on the head of a wearer, particularly under rapid acceleration.

30 The structural means is preferably formed of a thermoplastic material.

Preferably, the structural means comprising a left-handed helix and a right handed

helix, both helices being coaxial with the conduit. In comparison with known hoses
air conduits which have a structural means formed of a single helix, such a structural
means may have greater structural stability. This feature is also provided
separately.

5

Preferably, the helices are arranged such that, when the hose is compressed or
extended, substantially zero torque around the axis of the hose results. In this way,
if the user of the hose moves towards or away from an air source to which the hose
is attached, the likelihood of accidental detachment of the hose by rotation of the
10 attached end under a resultant torque and the risk of a kink forming in the hose may
be reduced.

Preferably, the structural means comprises a plurality of left-handed helices and/or
a plurality of right-handed helices. This may allow mechanical characteristics of the
15 hose (e.g. stiffness) to be tailored to particular applications.

Specific embodiments will now be described, by way of example only, with reference
to the accompanying drawings, in which:

20 Figure 1 shows an impact-resistant and energy absorbing helmet in use;

Figure 2 is a part section through the helmet shown in Figure 1 with mask, visor and
helmet-mounted equipment removed and showing a personalised cap;

25 Figure 3 shows a first hood adapted to be worn under the helmet shown in Figures
1 and 2;

Figure 4 shows a second hood adapted to be worn under the helmet shown in
Figures 1 and 2, illustrating the removable goggle and mask portion of the hood;

30

Figure 5 shows a further hood adapted to be worn over a helmet;

Figure 6 illustrates a helmet having a raisable visor, showing the visor in its raised position in dotted lines;

Figure 7 shows the hood of Figure 5 with the seal released and the visor of the helmet raised;

Figure 8 illustrates a hood having a sleeve for hoses for providing air to a respirator mask and demisting air;

Figure 9 is a schematic representation of a connection assembly at the distal end of the sleeve for connecting hoses running through the sleeve to an air supply of an aircraft;

Figure 10 is a part section through a first hose; and

Figure 11 is shows the structural helices of a second hose.

A first example of a system allowing a wearer of a helmet also to wear an environmental protection hood will first be described, in which the hood is to be worn under the helmet. A second example in which the hood is worn over the helmet will then be described, followed by further features which may be provided in connection with either example.

Figure 1 shows an impact-resistant and energy-absorbing helmet 2 of known multi-layer construction. A respiratory mask 4 is provided to allow the user to breathe in conditions where this would otherwise be difficult or impossible, and a visor 6 depending from a boss 7 is provided to shield the wearer's eyes.

Figure 2 is a schematic section through the helmet 2 with the mask 4, boss 7 and visor 6 removed,. The helmet comprises an outer shell 8 covering a personalised cap 10 comprising a crown portion 12 (to cover the crown of the head of a wearer of the helmet) and a brow portion 14 (to cover the brow). The crown and brow

portions 12, 14 of the cap 10 are contiguous with one another. The outer surfaces of the cap 10 are profiled to conform to the profile of the inner surface of the outer shell 8, such that relative movement of the cap 10 and the outer shell 8, when in use, is minimised.

5

The crown and brow portions 12, 14 of the cap 10 are formed in accordance with data relating to the size and shape of the head of an intended user of the helmet obtained by gauging the profile of the wearer's head, for example by a measurement device operating by direct measurement or by a non-contact method such as optical

10

scanning, without an environmental protection hood so that when the wearer for whom the helmet 2 was constructed wears the helmet without such a hood, it fits closely to his head, and the possibility of movement of the helmet relative to the head is minimized.

15

In addition, an alternative brow portion 14' (shown in dotted lines) of the cap 10 is provided. The outer surface of this alternative brow portion is also profiled to conform to the profile of the inner surface of the outer shell 8. However, the inner surface of the alternative brow portion 14' is formed in accordance with data relating to the size and shape of the head of the intended user of the helmet while wearing

20

an environmental protection hood so that when the wearer wears the helmet with such a hood, the helmet fits closely to his head and, again, the possibility of movement of the helmet relative to the head is minimized. In the preferred embodiment, the alternative brow portion 14' is shaped to accommodate a frame of the environmental protection hood (described in more detail below).

25

At the interface between the crown and brow portions 12, 14 of the cap 10, the portions engage with one another or interlock to inhibit relative movement of the portions during use of the helmet. However, the portions may be removed from the outer shell 8 independently of one another; in particular, the brow portions 14, 14'

30

of the cap may be interchanged without disturbing the crown portion.

Both portions of the cap 10 are formed of an energy or impact absorbing material

(for example, expanded polystyrene) in order to protect the wearer from injury in the event of an impact. Furthermore, the crown portion 12 of the cap is thicker than the brow portion 14, 14' and, in a particular embodiment, the portions are formed of different energy or impact absorbing materials having different impact properties.

5

The outer shell 8 of the helmet also comprises crown and brow portions 16, 18 respectively, which correspond approximately to the crown and brow portions of the cap 10. The outer radius of the shell brow portion 18 is less than that of the shell crown portion to permit the attachment over the brow portion of a helmet mounted display equipment. In conjunction with a thinner brow portion 14, 14' of the cap 10, this allows the display equipment to be mounted close to the eyes of the wearer of the helmet.

In the preferred embodiment, the measurement device by means of which data relating to the size and head of the intended wearer of the helmet is a non-contact device (for example which scans the head of the wearer of the helmet optically). In order to ensure accurate fitting of the helmet 2 and control over the attitude at which it sits upon the head of the wearer, the positions of the eyes of the wearer relative to one another and to the measured portion of his head are determined.

20

An environmental protection hood for use in conjunction with a helmet having the above-described personalised cap will now be described:

Figure 3 shows an environmental protection hood 40 to be worn under a helmet. The hood is formed of a flexible material and is adapted to be closing-fitting to the head of a wearer.

An aperture 42 in the flexible material is provided in a region of the hood intended to be situated in front of the eyes of the user when the hood is in use. The material of the hood at the periphery of the aperture is attached to a rigid frame 44, by means of which the shape of the aperture is maintained. The aperture is sealed by a removable clear window 46 through which a wearer of the hood may see.

Upper and lower clips 48, 50 are provided on the frame adjacent the brow and the cheeks respectively of a wearer of the hood for engaging with clips in a helmet such that the frame and the window are positively located relative to the helmet. In a preferred embodiment, the lower clips 50 are adapted to engage with mask receivers in a helmet under which the hood is worn.

The hood further comprises a mask region 52, intended to be situated adjacent a respiratory mask worn by the wearer of the hood, such that the mask is enclosed with the head of the wearer. At sides of the mask region, that is to say in locations on the inner surface of the hood, adjacent the cheeks or the ears of a wearer of the hood, there are provided receivers for receiving bayonets for locating the mask adjacent the mouth of the wearer. While the receivers may be attached to the frame, in a preferred embodiment the receivers are not attached the frame and the flexibility of the material between the receivers and the window allows the receivers to move relative to the window.

In a further embodiment, shown in Figure 4, the mask region of the hood is removable. In this embodiment, the frame 44 (the main frame) additionally defines an aperture 54 in the region of the mouth and nose of the wearer. The mask region of the hood comprises a further frame 56 (the mask frame) having a shape corresponding to that of the main frame such that the mask frame seals against the main frame. Clips are provided on the mask frame 56 which engage with the main frame 44 to positively locate and seal the mask frame against the main frame. In this embodiment, the lower clips 50 are provided on the mask frame 56.

The second example will now be described.

As indicated above, in this example, the hood is worn over a helmet for example as shown in Figure 1.

Figure 5 shows a hood 80 being worn over a helmet (such as that shown schematically in Figure 6). The hood is formed largely of a flexible material which

allows the hood conform to the shape of the helmet over which it is worn. A transparent window or visor 82 is provided in an eye region of the hood, through which the wearer of the hood may see. A releasable seal 84 is provided along or adjacent the lower edge of the visor 82. By releasing this seal, an opening may be
5 made in the hood.

Turning to Figure 6 an example of a helmet with which the hood may be worn comprises a head portion 92 and a helmet-mounted display unit or boss 94 mounted on the head portion at pivots 96 so that the boss may be raised from a first position
10 to a second position (shown in dotted lines). A transparent visor 98 depends from the boss 94.

When the hood 80 is worn with such a helmet 90, the hood visor 82 and the helmet visor 98 are both situated in front of the eyes of the wearer. Adjacent the periphery
15 of the hood visor 82 are provided clips which engage with the boss 94 to locate the visors 82, 98 in relation to one another. Thus, when the seal 84 is released, both the hood visor 82 and the helmet visor 98 may be raised together, as shown in Figure 7.

20 Turning to Figure 8, a system for providing air to a respiratory mask worn together with the hood will now be described. This system is applicable equally to the under-helmet hood 40 and the over-helmet hood 80 described above.

The hood 100 comprises a sleeve 102 formed of the same flexible material as the
25 main body of the hood. A hose 104 for feeding air to a respiratory mask 105 worn by the wearer of the hood is inserted into the sleeve and the proximal end of the hose 104 is connected to the mask in a known manner.

Also running through the sleeve is a further hose 106 for supplying demisting air to
30 the window 101 of the hood 100.

At the distal end of the sleeve is provided a connection assembly 110 (see Figure

9). The connection assembly comprises a socket 112 on the inside of the sleeve in flow communication with a plug 114 on the outside of the sleeve. The socket 112 is adapted to receive and retain the hose 104 for supplying air to the mask 105 (which may, for example, be as currently used to supply air to respiratory masks in aircraft) and the further hose 106 for supplying demisting air. The sleeve is sealed around the connection assembly 110, but air may pass into the hoses from the air supply of an aircraft via the connection assembly. In this way, air may be supplied to the mask 105 by means of a hose which is enclosed in the hood. In the case of a hood intended to be worn over a helmet, cables for power, data and communications also reach the helmet via a sleeve (for example, the sleeve 102 shown in Figures 8 and 9.

A hose suitable for use with the above-described systems will now be described with reference to Figures 10 and 11.

Figure 10 shows a first hose 120 comprising an enclosure means in the form of a silicone rubber wall 122 shown in cross-section, and structural means, for maintaining the structure of the hose, in the form of two coaxial helices, one 124 running inside the other 126. The inner helix 124 is right-handed while the outer helix 126 is left-handed, and their radii are similar such that there is contact between the helices where they cross one another. In some embodiments, the helices may be bonded to one another. Furthermore, the helices may float freely within the outer wall 122, they may be bonded to it along their length (for example, using a thin film adhesive), or they may be constrained relative to the wall at either or both ends.

The helices are formed of a thermoplastics material such as nylon, polyethylene or polypropylene by extrusion.

Figure 11 shows an alternative structural means 130 comprising a left-handed outer helix 132 around three right-handed inner helices 134, 136, 138. The inner helices 134, 136, 138 have smaller cross-sections (i.e. the cross-section of the material forming the helix, rather than of the helix itself) than the outer helix 132. The helices

are again of extruded thermoplastics material.

Further embodiments are possible having one or more helix in each direction, the helices being of various cross-sections and pitch and in various arrangements.

- 5 However, the cross-sections, pitch and arrangement of the helices are chosen so as to minimise the torque around the axis of the hose produced when the hose is compressed or stretched. For example, in the arrangement shown in Figure 10, the helices are of identical cross-section and identical pitch.

- 10 Each feature disclosed in the description, and/or the claims and drawings may be provided independently or in any appropriate combination. In particular, a feature of a subsidiary claim may be incorporated into a claim upon which it is not dependent.

CLAIMS

- 5 A1. A personalised cap for a helmet, the cap being bespoke to a specific wearer so as precisely to fit the helmet to the wearer's head, the cap comprising a crown portion and a separate brow portion, the crown and brow portion being contiguous with each other.
- 10 A2. A cap as claimed in claim A1, wherein the brow portion interlocks with the crown portion.
- A3. A cap as claimed in claim A1 or claim A2 wherein at least one said portion is of impact or energy absorbing material.
- 15 A4. A cap as claimed in claim A3, wherein the brow portion is thinner than the crown portion.
- A5. A cap as claimed in claim A4, wherein the brow portion is of a different impact or energy absorbing material to the crown portion.
- 20 A6. A helmet comprising a personalised cap as claimed in any of claims A1 to A5.
- A7. A helmet as claimed in claim A6 when dependent from claim 4 or claim 5, wherein a brow portion of the helmet is of a smaller radius than a crown portion to permit the attachment over the brow portion of a helmet mounted display equipment.
- 25 A8. A helmet as claimed in claim A6 or claim A7, wherein the brow portion is removable from the helmet without disturbing the crown portion, whereby one brow portion can be substituted for another.
- 30 A9. A method of manufacturing a helmet comprising a personalised internal cap which positions the helmet on the wearer's head, the method comprising a prior determination of the shape of the wearer's head by a measurement device followed

by the production of a kit of parts for assembly into said personalised cap, the kit comprising a crown portion and alternative brow portions, a first said brow portion conforming to the wearer's head when wearing an environmental protection hood, and a second said brow portion conforming to the wearer's head without said hood.

5

A10. A method as claimed in claim A9, wherein the measurement device is a non-contact measuring device.

A11. A method as claimed in claim A9 or claim A10, wherein during the prior
10 determination the relative positions of the wearer's eyes and the measured portion of his head are determined.

A12. A kit of parts for precisely fitting a helmet to a wearer's head, comprising a crown portion and first and second brow portions of a personalised internal cap
15 which position the helmet on the wearer's head, the first and second brow portions having respectively been produced to align the helmet on the wearer's head to a predetermined position relative to his eyes when the wearer respectively is wearing
and is not wearing an environmental protection hood.

20 A13. A method or a kit of parts according to any of claims A9 to A12, wherein the crown portion engages the first brow portion or the second brow portion to form the personalised internal cap.

A14. A method or a kit of parts as claimed in any preceding claim, wherein the first
25 brow portion is shaped to accommodate a visor of the environmental protection hood.

A15. A helmet comprising a personalised internal cap formed from a kit of parts as claimed in any of claims A12 to A14.

30

A16. Protective apparel comprising helmet as claimed in claim 15 or manufactured by a method according to any of claims A9 to A11, A13 or A14, in combination with

an environmental protection hood.

5 A17. A personalised cap, a kit of parts, a helmet and protective apparel substantially as hereinbefore described with reference to the accompanying drawings.

10 B1. An environmental protection hood for use under a protective helmet, comprising an aperture containing a window adjacent the periphery of which is provided means for engaging with an opening in a helmet.

B2. A hood as claimed in claim B1, wherein the window is reversibly removable from the hood.

15 B3. A hood as claimed in claim B2, comprising engaging means for engaging with and retaining the window.

B4. A hood as claimed in any of claims B1 to B3, further comprising a rigid frame.

20 B5. A hood as claimed in any of claims B1 to B4, further comprising fittings for engaging with a respiratory mask to locate such a mask when used by a wearer of the hood.

25 B6. A hood as claimed in any of claims B1 to B5, further comprising a removable mask portion.

B7. A hood as claimed in claim B6 when dependent upon claim B4, wherein the mask portion comprises a further rigid frame adapted to seal against the rigid frame.

30 B8. A mask as claimed in claim B6 or B7 when dependent upon claim B5, wherein the fittings are provided on the rigid frame of the mask portion.

C1. An environmental protection hood for use over a helmet and a respiratory

mask, the hood being adapted to entirely enclose the helmet and mask.

C2. A hood as claimed in claim C1, comprising an aperture having situated therein a window through which a wearer of the hood may see, a selectively
5 releasable seal being provided adjacent an edge of the window such that an opening may be made in the hood.

C3. An environmental protection hood for use over a helmet, comprising an aperture having situated therein a window through which a wearer of the hood may
10 see, a selectively releasable seal being provided adjacent an edge of the window such that an opening may be made in the hood.

C4. A hood as claimed in claim C2 or C3, further comprising means for engaging the window with a raisable front portion of a helmet, such that when the hood and
15 helmet are worn together, the window and the front portion of the helmet may be raised and lowered together.

C5. A hood as claimed in any of claims C2 to C4, further comprising fittings for engaging with a respiratory mask to locate such a mask when used by a wearer of
20 the hood.

C6. A hood according to any of claims B1 to B8 or C1 to C5 comprising a sleeve adapted to receive a hose for delivering air to a respiratory mask worn by a wearer of the hood.

25

C7. An environmental protection for use over a respiratory mask, comprising a sleeve adapted to receive a hose for delivering air to a respiratory mask worn by a wearer of the hood.

30 C8. A hood according to claim C6 or C7, wherein the sleeve is formed of the same material as the hood.

C9. - A hood according to any of claims C6 to C8, wherein the distal end of the sleeve with respect to the aperture of the hood has means inside the sleeve for engaging with a hose by means of which the hose may be fed with air.

5 C10. A hood according to claim C9, wherein the distal end of the sleeve has means outside the sleeve for engaging with an air supply means of an aircraft, by means of which the hose may be fed with air.

C11. A hood as claimed in any of claims C6 to C10, wherein the sleeve further
10 comprises at its distal end means for attaching a further hose for providing demisting air to the hood adjacent the head of a wearer.

C12. A hood according to claim C11, wherein a further hose for providing demisting air runs from the distal end of the sleeve to a portion of the hood adapted
15 in use to be adjacent the head of a wearer.

D1. A respiratory mask air supply hose comprising enclosure means forming a conduit through which air may pass and structural means for maintaining the cross-section of the conduit, the enclosure means being formed of different material.
20

D2. A hose as claimed in claim D1, wherein the enclosure means is formed of silicone rubber.

D3. A hose as claimed in claim D1 or D2, wherein the structural means is formed
25 of an extruded thermoplastics material.

D4. A hose as claimed in any of claims D1 to D3, wherein the structural means comprising a left-handed helix and a right handed helix, both helices being coaxial with the conduit.
30

D5. An air supply hose comprising enclosure means forming a conduit through which air may pass and structural means for maintaining the cross-section of the

conduit, wherein the structural means comprising a left-handed helix and a right handed helix, both helices being coaxial with the conduit.

5 D6. A hose as claimed in claim D4 or D5, wherein the helices are arranged such that, when the hose is compressed or extended, substantially zero torque around the axis of the hose results.

10 D7. A hose as claimed in any of claims D4 to D6, wherein the structural means comprises a plurality of left-handed helices and/or a plurality of right-handed helices.

D8. A hose substantially as hereinbefore described, with reference to and/or as illustrated in the accompanying drawings.

15 E1. A hood substantially as hereinbefore described with reference to, and/or as illustrated in, the accompanying drawings.

E2. A hose substantially as hereinbefore described with reference to, and/or as illustrated in, the accompanying drawings.

ABSTRACT

A personalised cap 10 for use with a protective helmet is disclosed, having crown and brow portions 12, 10. The brow portion 12 is removable independently of the
5 crown portion 10, and an alternative brow portion 12' is provided for use when a environmental protection hood is to be worn under the helmet.

A hood for use over a helmet and a hose for use to provide air to a respiratory mask are also disclosed.

10

[Figure 2]



Fig. 1.




Fig. 2




Fig. 3

4/11.




Fig. 14




Fig. 5




Fig. 6

7/11




Fig 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11

